





RoHS





短柄 Short handle



PCB Layout(Pattern Side)



Circuit Diagram



凸柄 Convex handle

NOTE:

- 1.Rating: 24V 25mA DC
- 2.Insulation Resistance:  $\geq 100 \text{ M}\Omega$
- 3.Withstand voltage: AC 500V 1Minute
- 4.Operating Force Range: 500gf Max
- 5.Mechanical Life: 3,000 Cycles

Ⓔ	Terminal		14	Brass	Gold plating
Ⓗ	Shrapnel		7	Beryllium copper	Gold plating
Ⓒ	Handle		7	PA46	White
Ⓑ	Cover		1	PPS	Black
Ⓐ	Base		1	PPS	Black
NO.	Name	Number	Qty	Materil	Remarks

Number of digits(位数)	1P	2P	3P	4P	5P	6P	7P	8P	9P	10P	12P
Cover/black 凸柄 盖子/黑色 短柄	TL-01 TL-01D	TL-02 TL-02D	TL-03 TL-03D	TL-04 TL-04D	TL-05 TL-05D	TL-06 TL-06D	TL-07 TL-07D	TL-08 TL-08D	TL-09 TL-09D	TL-10 TL-10D	TL-12 TL-12D

YUANDI® Yuandi Electronics Co, Ltd

design	date	name	DIP SWITCH
Review	date	model	
Approved	date	TL-07	

Drawing number: Proportion 1:1 unit mm gage number A4

modify Review Approved Tolerance not specified